

Crexendo® VIP Platform Desktop Devices



	T33G	CX530	CX540
Operating System		Linux Based	Linux Based
Interface			
LCD Display	2.4" 320x240 pixels color display	3.7" 360x160 pixels graphical display	4.3" 480x272 pixels color display
LCD Type	Adjustable	Adjustable	Adjustable
LED Indicator	√	√	√
Line Key	4	8	10
Memory Key	12 (4 pages, 3 keys per page)	21 (3 pages, 7 keys per page)	27 (3 pages, 9 keys per page)
USB Port (2.0 Compliant)	-	1	1
Ethernet Port	Dual-port Gigabit Ethernet	Dual-port Gigabit Ethernet	Dual-port Gigabit Ethernet
Handset Port (RJ-9)	√	√	√
Headset Port (RJ-9)	√	√	√
Expansion Module	-	Yealink EXP50	Yealink EXP50
External Yealink AC Adapter (Optional)	AC 100~240V input and DC 5V/2A output	AC 100~240V input and DC 5V/1.2A output	AC 100~240V input and DC 5V/2A output
Audio Features			
HD Voice	HD handset, HD speaker	HD handset, HD speaker	HD handset, HD speaker
Speakerphone	Full duplex	Full duplex	Full duplex
Wideband Codec	G.722,Opus	G.722,Opus	G.722,Opus
Narrowband Codec	G.711(A/μ), G.729A/B, G.726,G.723.1, iLBC, Opus	G.711(A/μ), G.729A/B, G.726, G.723.1, iLBC	G.711(A/μ), G.729A/B, G.726, G.723.1, iLBC
HAC Handset	√	√	√
Yealink Acoustic Shield	√	√	√
Connectivity			
PoE	√	√	√
Bluetooth	-	Built-in Bluetooth 4.2/T53 via BT40	Built-in Bluetooth 4.2
Wi-Fi	-	Built-in (2.4G and 5G)/T53 via WF40/WF50	Built-in 2.4G and 5G
Foot Stand	2 adjustable angles	1 adjustable angle	1 adjustable angle
Wall Mountable	√	√	√
Corded-Cordless Phone (via DD10K)	-	√	√
Headset	RJ9	USB/Bluetooth/RJ9	USB/Bluetooth/RJ9
Content Sharing	-	√	√
Telephony Features			
SIP Account	4	12	16
Audio Conferencing	5-Party Audio Conferencing	3-Way Audio Conferencing	3-Way Audio Conferencing

Crexendo® VIP Platform Desktop Devices



	T57W	T58W	T58W Pro
Operating System	Linux Based	Android 9.0	Android 9.0
Interface			
LCD Display	7" 800x480 pixels color display	7" 1024x600 pixels color touch screen	7" 1024x600 pixels color touch screen
LCD Type	Adjustable	Adjustable	Adjustable
LED Indicator	√	√	√
Line Key	0	0	0
Memory Key	29 touch keys	27 (3 pages, 9 keys per page)	27 (3 pages, 9 keys per page)
USB Port (2.0 Compliant)	1	2x USB A	2x USB A
Ethernet Port	Dual-port Gigabit Ethernet	Dual-port Gigabit Ethernet	Dual-port Gigabit Ethernet
Handset Port (RJ-9)	√	√	√
Headset Port (RJ-9)	√	√	√
Expansion Module	Yealink EXP50	3x Yealink EXP50	3x Yealink EXP50
External Yealink AC Adapter (Optional)	AC 100~240V input and DC 5V/2A output	AC 100~240V input and DC 5V/2A output	AC 100~240V input and DC 5V/2A output
Audio Features			
HD Voice	HD handset, HD speaker	HD handset, HD speaker	HD handset, HD speaker
Speakerphone	Full duplex	Full duplex	Full duplex
Wideband Codec	G.722,Opus	G.722,Opus	G.722,Opus
Narrowband Codec	G.711(A/μ), G.729A/B, G.726, G.723.1, iLBC	G.711(A/μ), G.729A/B, G.726,G.723.1, iLBC, Opus	G.711(A/μ), G.729A/B, G.726,G.723.1, iLBC, Opus
HAC Handset	√	√	√
Yealink Acoustic Shield	√	√	√
Connectivity			
PoE	√	√	√
Bluetooth	Built-in Bluetooth 4.2	Built-in Bluetooth 4.2	Built-in Bluetooth 4.2
Wi-Fi	Built-in 2.4G and 5G	Built-in 2.4G and 5G	Built-in 2.4G and 5G
Foot Stand	1 adjustable angle	1 adjustable angle	1 adjustable angle
Wall Mountable	√	√	√
Corded-Cordless Phone (via DD10K)	√	√	√
Headset	USB/Bluetooth/RJ9	USB/Bluetooth/RJ9	USB/Bluetooth/RJ9
Content Sharing	√	√	√
Telephony Features			
SIP Account	16	16	16
Audio Conferencing	3-Way Audio Conferencing	10-Party Audio Conferencing	10-Party Audio Conferencing