



Updated April 2017

CONTENTS

FLOOR-STANDING RACK ENCLOSURES		PAGE
42U-48U Standard-Width, Standard-Depth Cabinets	Recommended for low/medium-density server applications.	2
25U-48U Standard-Width, Standard-Depth Shock Pallet Cabinets	Recommended for shipping with equipment installed.	2
12U-25U Compact Standard-Width Cabinets	Recommended for remote/back office server applications.	2
42U-48U Standard-Width, Standard-Depth Colocation Cabinets	Recommended for multi-tenant installations in shared spaces.	2
42U Standard-Width Value Series Cabinets	Recommended for low/medium-density server applications with constricted budgets.	2
42U-48U Extra-Wide, Standard-Depth Cabinets	Recommended for networking and blade server applications.	3
42U-48U Extra-Deep, Standard-Width Cabinets	Recommended for medium/high-density server applications.	3
42U-48U Extra-Deep and Extra-Wide Cabinets	Recommended for high-density networking and blade server applications.	3
42U-45U Mid-Depth, Standard-Width Cabinets	Recommended for low/medium-density, space-limited server applications.	3
25U-45U Shallow-Depth, Standard-Width Cabinets	Recommended for audio/video applications.	3
12U-42U NEMA-Rated and Seismic-Certified Cabinets	Recommended for harsh commercial/industrial environments and earthquake zones.	3
WALL-MOUNT RACK ENCLOSURES & OPEN FRAME RACKS		
12U-18U Patch-Depth Cabinets	Recommended for equipment up to 13" deep.	4
6U-21U Switch-Depth Cabinets	Recommended for equipment up to 16.5" deep.	4
6U-26U Switch-Depth+ Cabinets	Recommended for equipment up to 20.5" deep.	4
12U-26U UPS-Depth Cabinets	Recommended for equipment up to 24.5" deep.	5
12U Server-Depth Cabinets	Recommended for equipment up to 32.5" deep.	5
12U-18U Side-Mount Server-Depth Cabinets	Recommended for equipment up to 32.5" deep.	5
2U-6U Vertical-Mount Switch-Depth+ Cabinets	Recommended for equipment up to 20" deep in shallow spaces.	5
2U-16U Vertical-Mount Server-Depth Cabinets	Recommended for equipment up to 36" deep in shallow spaces.	5
5U DVR Lockbox	Recommended for rack-mount and non-rack-mount security DVRs.	5
2U-22U Wall-Mount Open Frame Racks	Recommended for compact installations in secure areas.	5
FLOOR-STANDING OPEN FRAME RACKS		
12U-45U 2-Post Racks	Recommended for networking applications in secure areas.	6
12U-45U Standard-Depth 4-Post Racks	Recommended for server and networking applications in secure areas.	6
48U-58U Heavy-Duty Standard-Depth 4-Post Racks	Recommended for high-density server and networking applications in secure areas.	6
42U-48U Premium Heavy-Duty Standard-Depth 4-Post Racks	Recommended for high-density server and networking applications in secure areas.	6
42U-45U Premium Heavy-Duty Mid-Depth 4-Post Racks	Recommended for space-limited server and networking applications in secure areas.	6
COOLING SOLUTIONS & ACCESSORIES		
Close-Coupled, Self-Contained Air Conditioners	Rack-mount, wall-mount, portable and row-based air conditioning with network management support.	7
Air Conditioner Accessories	Configuration kits, network management cards and environmental sensors.	7
Chilled Water Cooling Solutions	Row-based chilled water cooling for medium- and high-density rack environments.	7
Active Airflow Management	High-performance fans for rack enclosure heat removal.	7
Passive Airflow Management	Blanking panels, ducts and gaskets to prevent warm air recirculation and increase cooling efficiency.	7
RACK ACCESSORIES		
Vertical Cable Managers	Keep cables organized to help prevent airflow obstructions and facilitate troubleshooting and changes.	8
Horizontal Cable Managers	Route cables from vertical cable channels across the rack to equipment ports and patch panels.	8
Overhead Cable Managers	Route cables between racks, across aisles and over open spaces.	8
Cable Ties	Bundle and secure cables.	8
Shelves	Provide stable storage and convenient accessibility for non-rack equipment in 2-post and 4-post racks.	8
Side Panels	Cover open rack sides to prevent warm air recirculation, restrict access and streamline appearance.	8
Configuration Accessories	Adapt racks for alternate/additional applications.	9
Mounting Accessories	Mounting hardware, brackets, rails, adapters and grounding kits.	9
Security & Environmental Monitoring Accessories	Locks, sensors and remote management cards.	9
OTHER RACK-MOUNT IT SOLUTIONS		
Basic Rack PDUs	Reliable power distribution.	10
Metered Rack PDUs	Reliable power distribution and current/load monitoring.	10
Monitored Rack PDUs	Reliable power distribution, current/load monitoring and network interface.	10
Switched Rack PDUs	Reliable power distribution, current/load monitoring, network interface and remote outlet control.	10
Rack Consoles	LCD console folds and slides into 1U drawer for compact storage and rack-side access.	11
Console KVM Switches	KVM switch with LCD console folds and slides into 1U drawer for compact storage and rack-side access.	11
SmartPro® UPS Systems	Line-interactive operation (AVR), sine wave output, battery backup and network card slot.	11
SmartOnline® UPS Systems	On-line operation (double conversion), sine wave output, battery backup and network card slot.	11
SmartOnline Hot-Swappable UPS Systems	On-line operation (double conversion), sine wave output, battery backup, network card slot and bypass switch.	11
Copper Patch Panels	Reliable, compatible, space-saving connections for UTP/STP Ethernet patch cables.	12
Fiber Patch Panels	Reliable, compatible, space-saving connections for multimode and singlemode fiber-optic patch cables.	12
Modular Patch Panels	Future-proof high-density network connections with modular media cassettes (copper and fiber).	12

Floor-Standing Rack Enclosures

Model	EIA-Compliant Rack Spaces	Maximum Device Depth	Front/Rear Doors	Acrylic "Glass" Door/Window	Side Panels	Roof or Roof Panel	Stationary Weight Capacity	Rolling Weight Capacity	Casters/Levelers (HD: 3" Casters)	Color (BL=Black, WH=White)	Unit Height	Unit Width	Unit Depth	Unit Weight	Shock Pallet Packaging ¹	Equipment Mounting Holes (Square or Round/Threaded)	Assembled ² (KD=Knockdown ³)	IP Rating (IP54=NEMA 12)	Seismic Rating	Air Filter(s) and Ventilation Fan(s)	TAA Compliant
42U-48U Standard-Width, Standard-Depth Cabinets – Recommended for low/medium-density server applications.																					
SR42UB	42U	37"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	78.5"	23.63"	43"	281 lb	No	Square	Yes	IP20	No	No	No
SR42UBTAA	42U	37"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	78.5"	23.63"	43"	286 lb	No	Square	Yes	IP20	No	No	TAA
SR42UW	42U	37"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	WH	78.5"	23.63"	43"	286 lb	No	Square	Yes	IP20	No	No	No
SR42UB1032	42U	37"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	78.5"	23.63"	43"	286 lb	No	Round	Yes	IP20	No	No	No
SR42UBG	42U	37"	Yes	Yes	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	78.5"	23.63"	43"	286 lb	No	Square	Yes	IP20	No	No	No
SR42UBEXP	42U	37"	Yes	No	No	Yes	3000 lb	2250 lb	Yes	BL	78.5"	23.63"	43"	203 lb	No	Square	Yes	IP00	No	No	No
SR42UWEXP	42U	37"	Yes	No	No	Yes	3000 lb	2250 lb	Yes	WH	78.5"	23.63"	43"	209 lb	No	Square	Yes	IP00	No	No	No
SR42UBKD	42U	37"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	78.5"	23.63"	43"	281 lb	No	Square	KD	IP20	No	No	No
SR45UB	45U	37"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	83.75"	23.63"	43"	307 lb	No	Square	Yes	IP20	No	No	No
SR45UBEXP	45U	37"	Yes	No	No	Yes	3000 lb	2250 lb	Yes	BL	83.75"	23.63"	43"	223 lb	No	Square	Yes	IP00	No	No	No
SR48UB	48U	37"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	89"	23.63"	43"	309 lb	No	Square	Yes	IP20	No	No	No
SR48UBEXP	48U	37"	Yes	No	No	Yes	3000 lb	2250 lb	Yes	BL	89"	23.63"	43"	211 lb	No	Square	Yes	IP00	No	No	No
25U-48U Standard-Width, Standard-Depth Shock Pallet Cabinets¹ – Recommended for shipping with equipment installed.																					
SR25UBSP1	25U	37"	Yes	No	Yes (2)	Yes	3000 lb	2250 lb	Yes	BL	49"	23.63"	43"	195 lb	Yes	Square	Yes	IP20	No	No	No
SR42UBSP1	42U	37"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	78.5"	23.63"	43"	286 lb	Yes	Square	Yes	IP20	No	No	No
SR42UWSP1	42U	37"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	WH	78.5"	23.63"	43"	286 lb	Yes	Square	Yes	IP20	No	No	No
SR45UBSP1	45U	37"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	83.75"	23.63"	43"	307 lb	Yes	Square	Yes	IP20	No	No	No
SR48UBSP1	48U	37"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	89"	23.63"	43"	315 lb	Yes	Square	Yes	IP20	No	No	No
12U-25U Compact Standard-Width Cabinets – Recommended for remote/back office server applications.																					
SR12UB	12U	32.5"	Yes	No	Yes (2)	Yes	1000 lb	1000 lb	Yes	BL	25.1"	23.63"	33.5"	105 lb	No	Square	Yes	IP20	No	No	No
SR18UB	18U	32.5"	Yes	No	Yes (2)	Yes	1000 lb	1000 lb	Yes	BL	35.6"	23.63"	33.5"	105 lb	No	Square	Yes	IP20	No	No	No
SR24UB	24U	32.5"	Yes	No	Yes (2)	Yes	1000 lb	1000 lb	Yes	BL	45.6"	23.63"	33.5"	123 lb	No	Square	Yes	IP20	No	No	No
SR25UB	25U	37"	Yes	No	Yes (2)	Yes	3000 lb	2250 lb	Yes	BL	49"	23.63"	43"	195 lb	No	Square	Yes	IP20	No	No	No
SR25UBEXP	25U	37"	Yes	No	No	Yes	3000 lb	2250 lb	Yes	BL	49"	23.63"	43"	163 lb	No	Square	Yes	IP20	No	No	No
SR25UBKD	25U	37"	Yes	No	Yes (2)	Yes	3000 lb	2250 lb	Yes	BL	49"	23.63"	43"	195 lb	No	Square	KD	IP20	No	No	No
SR25UBTAA	25U	37"	Yes	No	Yes (2)	Yes	3000 lb	2250 lb	Yes	BL	49"	23.63"	43"	195 lb	No	Square	Yes	IP20	No	No	TAA
42U-48U Standard-Width, Standard-Depth Colocation Cabinets – Recommended for multi-tenant installations in shared spaces.																					
SR42UBCL	42U ⁴	37"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	78.5"	23.63"	43"	305 lb	No	Square	Yes	IP20	No	No	No
SR48UBCL	48U ⁵	37"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	89"	23.63"	43"	334 lb	No	Square	Yes	IP20	No	No	No
42U Standard-Width Value Series Cabinets – Recommended for low/medium-density server applications with constricted budgets.																					
SR2000	42U	35"	Yes	No	Yes (2)	Yes	2000 lb	1100 lb	Yes	BL	77.67"	23.63"	39.37"	170 lb	No	Square	Yes	IP20	No	No	No
SR2400	42U	37"	Yes	No	Yes (4)	Yes	2400 lb	1600 lb	Yes	BL	78.5"	23.63"	43"	260 lb	No	Square	Yes	IP20	No	No	No

Standards include EIA/ECA-310-E, IEC 60297-3-100, DIN 41494, UL 60950, NOM and RoHS. Standards may vary with model. Most racks include a 5-year limited warranty. See tripplite.com for details. (1) Enclosures with shock pallet packaging can be shipped with rack-mount equipment pre-installed – up to 1250 lb including the weight of the enclosure. (2) Includes models that require minimal assembly, such as installing side panels. (3) Knockdown models are disassembled into key sub-assemblies for compact transport and assembly in confined spaces. (4) Two separate 20U compartments for equipment. (5) Two separate 23U compartments for equipment.



Find it fast! Try our interactive rack selector at www.tripplite.com/rack or contact our application team at **773.869.1236** or solutions@tripplite.com.

Floor-Standing Rack Enclosures

Model	EIA-Compliant Rack Spaces	Maximum Device Depth	Front/Rear Doors	Acrylic "Glass" Door/Window	Side Panels	Roof or Roof Panel	Stationary Weight Capacity	Rolling Weight Capacity	Casters/Levelers (HD: 3" Casters)	Color (BL=Black, WH=White)	Unit Height	Unit Width	Unit Depth	Unit Weight	Shock Pallet Packaging ¹	Equipment Mounting Holes (Square or Round/Threaded)	Assembled ² (KD=Knockdown ³)	IP Rating (IP54=NEMA 12)	Seismic Certification	Air Filter(s) and Ventilation Fan(s)	TAA Compliant
42U-48U Extra-Wide, Standard-Depth Cabinets – Recommended for networking and blade server applications.																					
SR42UBWD	42U	37"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	78.5"	29.53"	43"	315 lb	No	Square	Yes	IP20	No	No	No
SR42UBWDSP1	42U	37"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	78.5"	29.53"	43"	315 lb	Yes	Square	Yes	IP20	No	No	No
SR42UBWDVRT ⁴	42U	37"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	78.5"	29.53"	43"	345 lb	No	Square	Yes	IP20	No	No	No
SR45UBWD	45U	37"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	83.75"	29.53"	43"	340 lb	No	Square	Yes	IP20	No	No	No
SR45UBWDSP1	45U	37"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	83.75"	29.53"	43"	340 lb	Yes	Square	Yes	IP20	No	No	No
SR45UBWDVRT ⁴	45U	37"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	83.75"	29.53"	43"	340 lb	No	Square	Yes	IP20	No	No	No
SR48UBWD	48U	37"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	89"	29.53"	43"	343 lb	No	Square	Yes	IP20	No	No	No
SR48UBWDSP1	48U	37"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	89"	29.53"	43"	343 lb	Yes	Square	Yes	IP20	No	No	No
42U-48U Extra-Deep, Standard-Width Cabinets – Recommended for medium/high-density server applications.																					
SR42UBDP	42U	42"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	78.5"	23.63"	47.25"	315 lb	No	Square	Yes	IP20	No	No	No
SR45UBDP	45U	42"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	83.75"	23.63"	47.25"	340 lb	No	Square	Yes	IP20	No	No	No
SR48UBDP	48U	42"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	89"	23.63"	47.25"	345 lb	No	Square	Yes	IP20	No	No	No
42U-48U Extra-Deep and Extra-Wide Cabinets – Recommended for high-density networking and blade server applications.																					
SR42UBDPWD	42U	42"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	78.5"	29.53"	47.25"	345 lb	No	Square	Yes	IP20	No	No	No
SR45UBDPWD	45U	42"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	83.75"	29.53"	47.25"	370 lb	No	Square	Yes	IP20	No	No	No
SR48UBDPWD	48U	42"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	89"	29.53"	47.25"	378 lb	No	Square	Yes	IP20	No	No	No
42U-45U Mid-Depth, Standard-Width Cabinets – Recommended for low/medium-density, space-limited server applications.																					
SR42UBMD	42U	31"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	78.5"	23.63"	36"	250 lb	No	Square	Yes	IP20	No	No	No
SR42UBMDEXP	42U	31"	Yes	No	No	Yes	3000 lb	2250 lb	Yes	BL	78.5"	23.63"	36"	186 lb	No	Square	Yes	IP00	No	No	No
SR45UBMD	45U	31"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	83.75"	23.63"	36"	285 lb	No	Square	Yes	IP20	No	No	No
25U-45U Shallow-Depth, Standard-Width Cabinets – Recommended for audio/video applications.																					
SR25UBSD3	25U	27"	Yes	No	Yes (2)	Yes	3000 lb	3000 lb	HD	BL	50"	23.63"	32.6"	190 lb	No	Square	Yes	IP20	No	No	No
SR42UBSD	42U	27"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	78.5"	23.63"	32.5"	215 lb	No	Square	Yes	IP20	No	No	No
SR42UBSD1032	42U	27"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	78.5"	23.63"	32.5"	215 lb	No	Round	Yes	IP20	No	No	No
SR45UBSD	45U	27"	Yes	No	Yes (4)	Yes	3000 lb	2250 lb	Yes	BL	83.75"	23.63"	32.5"	232 lb	No	Square	Yes	IP20	No	No	No
12U-42U NEMA-Rated and Seismic-Certified Cabinets – Recommended for harsh commercial/industrial environments and earthquake zones.																					
SR12UBFFD	12U	32.5"	Yes	No	Yes (2)	Yes	1000 lb	1000 lb	Yes	BL	25.2"	23.63"	38.5"	96 lb	No	Square	Yes	IP54	No	Yes	No
SR24UBFFD	24U	32.5"	Yes	No	Yes (2)	Yes	1000 lb	1000 lb	Yes	BL	46.8"	23.63"	38.5"	210 lb	No	Square	Yes	IP54	No	Yes	No
SR42UBEIS	42U	37"	Yes	No	Yes (4)	Yes	3000 lb	3000 lb	HD	BL	79.8"	23.63"	43"	310 lb	No	Square	Yes	IP54	No	Yes	No
SR42UBZ4	42U	37"	Yes	No	Yes (4)	Yes	3000 lb	–	No	BL	78.5"	23.63"	43"	353 lb	No	Square	Yes	IP20	Z4	No	No

Standards include EIA/ECA-310-E, IEC 60297-3-100, DIN 41494, UL 60950, NOM and RoHS. Standards may vary with model. Most racks include a 5-year limited warranty. See tripplite.com for details. (1) Enclosures with shock pallet packaging can be shipped with rack-mount equipment pre-installed – up to 1250 lb including the weight of the enclosure. (2) Includes models that require minimal assembly, such as installing side panels. (3) Knockdown models are disassembled into key sub-assemblies for compact transport and assembly in confined spaces. (4) Includes pre-installed SRCABLEVRT3.



Find it fast! Try our interactive rack selector at www.trippelite.com/rack or contact our application team at **773.869.1236** or solutions@trippelite.com.

Wall-Mount Rack Enclosures & Open Frame Racks

Model	EIA-Compliant Rack Spaces	Maximum Device Depth	Acrylic "Glass" Door/Window	Low-Profile ¹	Hinged Back (Side to Wall)	Closed Back (Side to Wall)	Removable Side Panels (2)	Weight Capacity	Color (BL=Black, WH=White)	Unit Height	Unit Width	Unit Depth	Unit Weight	Compatible with Casters	Equipment Mounting Holes (Square or Round/Threaded)	Assembled ² (KD=Knockdown ³)	IP Rating (IP54=NEMA 12)	Air Filter(s) and Ventilation Fan(s)	TAA Compliant
12U-18U Patch-Depth Cabinets – Recommended for equipment up to 13" deep.																			
SRW12U13	12U	13"	No	Yes	No	No	Yes	200 lb	BL	25.1"	23.63"	13"	38 lb	Yes	Both	Yes	IP20 ⁴	No	No
SRW12U13G	12U	13"	Yes	Yes	No	No	Yes	200 lb	BL	25.1"	23.63"	13"	38 lb	Yes	Both	Yes	IP20 ⁴	No	No
SRW18US13	18U	13"	No	Yes	Yes	Yes	Yes	250 lb	BL	35.6"	23.63"	13"	83.8 lb	Yes	Both	Yes	IP20 ⁴	No	No
SRW18US13G	18U	13"	Yes	Yes	Yes	Yes	Yes	250 lb	BL	35.6"	23.63"	13"	83.8 lb	Yes	Both	Yes	IP20 ⁴	No	No
6U-21U Switch-Depth Cabinets – Recommended for equipment up to 16.5" deep.																			
SRW6U	6U	16.5"	No	Yes	No	No	Yes	200 lb	BL	14.5"	23.63"	17.5"	29 lb	Yes	Both	Yes	IP20 ⁴	No	No
SRW6UG	6U	16.5"	Yes	Yes	No	No	Yes	200 lb	BL	14.5"	23.5"	17.5"	29 lb	Yes	Both	Yes	IP20 ⁴	No	No
SRW6UKD	6U	16.5"	No	Yes	No	No	Yes	200 lb	BL	14.45"	23.63"	17.94"	29 lb	Yes	Both	KD	IP20 ⁴	No	No
SRW6UW	6U	16.5"	No	Yes	No	No	Yes	200 lb	WH	14.5"	23.5"	17.5"	29 lb	Yes	Both	Yes	IP20 ⁴	No	No
SRW6UWG	6U	16.5"	Yes	Yes	No	No	Yes	200 lb	WH	14.5"	23.5"	17.5"	29 lb	Yes	Both	Yes	IP20 ⁴	No	No
SRW9U	9U	16.5"	No	Yes	No	No	Yes	200 lb	BL	19.88"	23.63"	17.78"	35 lb	Yes	Both	Yes	IP20 ⁴	No	No
SRW9UG	9U	16.5"	Yes	Yes	No	No	Yes	200 lb	BL	19.75"	23.63"	17.69"	34.6 lb	Yes	Both	Yes	IP20 ⁴	No	No
SRW12U	12U	16.5"	No	Yes	No	No	Yes	200 lb	BL	25.08"	23.63"	17.69"	48.5 lb	Yes	Both	Yes	IP20 ⁴	No	No
SRW12UG	12U	16.5"	Yes	Yes	No	No	Yes	200 lb	BL	25.08"	23.63"	17.69"	48.5 lb	Yes	Both	Yes	IP20 ⁴	No	No
SRW21U	21U	16.5"	No	Yes	No	No	Yes	200 lb	BL	40.87"	23.63"	17.72"	51 lb	Yes	Both	Yes	IP20 ⁴	No	No
SRW21UG	21U	16.5"	Yes	Yes	No	No	Yes	200 lb	BL	40.87"	23.63"	17.72"	51.2 lb	Yes	Both	Yes	IP20 ⁴	No	No
6U-26U Switch-Depth+ Cabinets – Recommended for equipment up to 20.5" deep.																			
SRW6UDP	6U	20.5"	No	Yes	No	No	Yes	200 lb	BL	14.57"	23.63"	21.71"	45.2 lb	Yes	Both	Yes	IP20 ⁴	No	No
SRW9UDP	9U	20.5"	No	Yes	No	No	Yes	200 lb	BL	19.83"	23.63"	21.71"	51.8 lb	Yes	Both	Yes	IP20 ⁴	No	No
SRW10US	10U	20.5"	No	Yes	Yes	Yes	Yes	200 lb	BL	21.57"	23.63"	21.6"	55 lb	Yes	Both	Yes	IP20	No	No
SRW10USG	10U	20.5"	Yes	Yes	Yes	Yes	Yes	200 lb	BL	21.56"	23.63"	21.63"	53.4 lb	Yes	Both	Yes	IP20	No	No
SRW12UDP	12U	20.5"	No	Yes	No	No	Yes	200 lb	BL	25.08"	23.63"	21.75"	58.4 lb	Yes	Both	Yes	IP20 ⁴	No	No
SRW12US	12U	20.5"	No	Yes	Yes	Yes	Yes	200 lb	BL	25"	23.63"	21.6"	60 lb	Yes	Both	Yes	IP20	No	No
SRW12USG	12U	20.5"	Yes	Yes	Yes	Yes	Yes	200 lb	BL	25"	23.63"	21.6"	60 lb	Yes	Both	Yes	IP20	No	No
SRW12USNEMA	12U	20.5"	No	Yes	Yes	Yes	Yes	200 lb	BL	25"	23.63"	21.6"	60 lb	Yes	Both	Yes	IP54	Yes	No
SRW15US	15U	20.5"	No	Yes	Yes	Yes	Yes	200 lb	BL	30.33"	23.63"	21.6"	88.2 lb	Yes	Both	Yes	IP20	No	No
SRW15USG	15U	20.5"	Yes	Yes	Yes	Yes	Yes	200 lb	BL	30.33"	23.63"	21.6"	88.2 lb	Yes	Both	Yes	IP20	No	No
SRW18US	18U	20.5"	No	Yes	Yes	Yes	Yes	250 lb	BL	35.6"	23.63"	21.6"	96 lb	Yes	Both	Yes	IP20	No	No
SRW18USG	18U	20.5"	Yes	Yes	Yes	Yes	Yes	250 lb	BL	35.6"	23.63"	21.6"	96 lb	Yes	Both	Yes	IP20	No	No
SRW26US	26U	20.5"	No	Yes	Yes	Yes	Yes	250 lb	BL	49.7"	23.63"	21.6"	125 lb	Yes	Both	Yes	IP20	No	No
SRW26USG	26U	20.5"	Yes	Yes	Yes	Yes	Yes	250 lb	BL	49.7"	23.63"	21.6"	125 lb	Yes	Both	Yes	IP20	No	No

Standards include EIA/ECA-310-E, IEC 60297-3-100, DIN 41494, UL 60950, NOM and RoHS. Standards may vary with model. Most racks include a 5-year limited warranty. See triplite.com for details. (1) Low-profile units extend no more than 25" from the wall. (2) Includes models that require minimal assembly, such as installing side panels. (3) Knockdown models are disassembled into key sub-assemblies for compact transport and assembly in confined spaces. (4) IP20 when mounted to wall; IP00 otherwise.



Find it fast! Try our interactive rack selector at www.triplite.com/wall-mount or contact our application team at **773.869.1236** or solutions@triplite.com.

Wall-Mount Rack Enclosures & Open Frame Racks

Model	EIA-Compliant Rack Spaces	Maximum Device Depth	Acrylic "Glass" Door/Window	Low-Profile ¹	Hinged Back (Side to Wall)	Closed Back (Side to Wall)	Removable Side Panels (2)	Weight Capacity	Color (BL=Black, WH=White)	Unit Height	Unit Width	Unit Depth	Unit Weight	Compatible with Casters	Equipment Mounting Holes (Square or Round/Threaded)	Assembled ² (KD=Knockdown ³)	IP Rating (IP54=NEMA 12)	Air Filter(s) and Ventilation Fan(s)	TAA Compliant
12U-26U UPS-Depth Cabinets – Recommended for equipment up to 24.5" deep.																			
SRW12USDP	12U	24.5"	No	No	Yes	Yes	Yes	200 lb	BL	25.06"	23.63"	25.5"	63.5 lb	Yes	Both	Yes	IP20	No	No
SRW12USDPG	12U	24.5"	Yes	No	Yes	Yes	Yes	200 lb	BL	25.06"	23.63"	25.5"	64 lb	Yes	Both	Yes	IP20	No	No
SRW18USDP	18U	24.5"	No	No	Yes	Yes	Yes	250 lb	BL	35.61"	23.5"	25.98"	100.9 lb	Yes	Both	Yes	IP20	No	No
SRW18USDPG	18U	24.5"	Yes	No	Yes	Yes	Yes	250 lb	BL	35.61"	23.5"	25.98"	99.6 lb	Yes	Both	Yes	IP20	No	No
SRW26USDP	26U	24.5"	No	No	Yes	Yes	Yes	250 lb	BL	49.63"	23.63"	25.51"	124.9 lb	Yes	Both	Yes	IP20	No	No
SRW26USDPG	26U	24.5"	Yes	No	Yes	Yes	Yes	250 lb	BL	49.63"	23.63"	25.51"	123.7 lb	Yes	Both	Yes	IP20	No	No
12U Server-Depth Cabinets – Recommended for equipment up to 32.5" deep.																			
SRW12US33	12U	32.5"	No	No	Yes	Yes	Yes	250 lb	BL	25"	23.63"	33.5"	100 lb	Yes	Both	Yes	IP20	No	No
SRW12US33G	12U	32.5"	Yes	No	Yes	Yes	Yes	250 lb	BL	25"	23.63"	33.5"	94.5 lb	Yes	Both	Yes	IP20	No	No
12U-18U Side-Mount Server-Depth Cabinets – Recommended for equipment up to 32.5" deep.																			
SRW12UHD	12U	32.5"	No	Yes	No	No	Yes ⁴	500 lb	BL	26.46"	36.2"	24.77"	101.4 lb	No	Both	Yes	IP20 ⁵	No	No
SRW18UHD	18U	32.5"	No	Yes	No	No	Yes ⁴	500 lb	BL	36.96"	36.22"	24.77"	119.9 lb	No	Both	Yes	IP20 ⁵	No	No
2U-6U Vertical-Mount Switch-Depth+ Cabinets – Recommended for equipment up to 20" deep in shallow spaces.																			
SRWF2U	2U ⁶	20"	No	Yes	No	Yes	No	150 lb	BL	28.8"	25.6"	4.5"	51.4 lb	No	Round	Yes	IP20	No	No
SRWF4U	4U ⁶	20"	No	Yes	No	Yes	No	150 lb	BL	28.8"	25.6"	8"	60.18 lb	No	Round	Yes	IP20	No	No
SRWF5U	5U ⁶	20"	No	Yes	No	Yes	No	150 lb	BL	28.8"	25.6"	9.7"	62 lb	No	Round	Yes	IP20	No	No
SRWF6U	6U ⁶	20"	No	Yes	No	Yes	No	150 lb	BL	28.8"	25.6"	11.5"	64 lb	No	Round	Yes	IP20	No	No
2U-16U Vertical-Mount Server-Depth Cabinets – Recommended for equipment up to 36" deep in shallow spaces.																			
SRWF2U36	2U ⁶	36"	No	Yes	No	Yes	No	150 lb	BL	43"	25.6"	4.5"	58.86 lb	No	Round	Yes	IP20	No	No
SRWF4U36	4U ⁶	36"	No	Yes	No	Yes	No	150 lb	BL	43"	25.6"	8"	66.13 lb	No	Round	Yes	IP20	No	No
SRWF5U36	5U ⁶	36"	No	Yes	No	Yes	No	150 lb	BL	43.2"	25.6"	9.7"	74 lb	No	Round	Yes	IP20	No	No
SRWF6U36	6U ⁶	36"	No	Yes	No	Yes	No	150 lb	BL	43"	25.6"	11.5"	88.2 lb	No	Round	Yes	IP20	No	No
SRWF12U38 ⁷	12U ⁷	35"	No	Yes	No	Yes	No	400 lb	BL	38"	19.69"	16.16"	66.8 lb	No	Round	Yes ⁷	IP20	No	No
SRWF16U38 ⁷	16U ⁷	35"	No	Yes	No	Yes	No	400 lb	BL	38"	19.69"	23.19"	81.5 lb	No	Round	Yes ⁷	IP20	No	No
5U DVR Lockbox – Recommended for rack-mount and non-rack-mount security DVRs.																			
SRDURLB	5U	16.25"	No	Yes	No	Yes	No	60 lb	BL	10"	24.3"	18.4"	28.7 lb	No	Square	Yes	IP20	Yes	No
2U-22U Wall-Mount Open Frame Racks – Recommended for compact installations in secure areas.																			
N060-002	2U	5.5"	No	Yes	No	No	No	17 lb	BL	3.5"	19"	6"	2.5 lb	No	Round	Yes	IP00	No	No
N060-004	4U	5.5"	No	Yes	No	No	No	35 lb	BL	7"	19"	6"	5 lb	No	Round	Yes	IP00	No	No
SRW012UHD	12U	18"	No	Yes	No	No	No	200 lb	BL	24.8"	20.1"	18.24"	14.3 lb	No	Round	No	IP00	No	No
SRW012US	12U	18"	No	Yes	Yes	No	No	150 lb	BL	31.04"	19.76"	20.35"	15 lb	No	Round	No	IP00	No	No
SRW08U22SD	8-22U ⁸	5.75"	No	Yes	No	No	No	150 lb	BL	42.3" ⁸	20.11"	6"	14.1 lb ⁸	No	Round	No	IP00	No	No
SRW08U22MD	8-22U ⁸	11.5"	No	Yes	No	No	No	150 lb	BL	42.3" ⁸	20.11"	12"	14.8 lb ⁸	No	Round	No	IP00	No	No
SRW08U22	8-22U ⁸	18"	No	Yes	No	No	No	150 lb	BL	42.3" ⁸	20.11"	18.24"	15.03 lb ⁸	No	Round	No	IP00	No	No
SRW08U22DP	8-22U ⁸	23.5"	No	Yes	No	No	No	150 lb	BL	42.3" ⁸	20.11"	24"	17.2 lb ⁸	No	Round	No	IP00	No	No

Standards include EIA/ECA-310-E, IEC 60297-3-100, DIN 41494, UL 60950, NOM and RoHS. Standards may vary with model. Most racks include a 5-year limited warranty. See triplite.com for details. (1) Low-profile units extend no more than 25" from the wall. (2) Includes models that require minimal assembly, such as installing side panels. (3) Knockdown models are disassembled into key sub-assemblies for compact transport and assembly in confined spaces. (4) Side-mount models have a single side panel. (5) IP20 when mounted to wall; IP00 otherwise. (6) Also has a bracket for patch panels, which is not included in the total number of rack spaces. 2U enclosures have a 1U bracket. 4U-6U enclosures have a 2U bracket. (7) The cabinet can be mounted to a wall or a 2-post rack. It has a 4U bracket for patch panels, which is included in the total number of rack spaces. Although the cabinet ships assembled, mounting may require partial disassembly. (8) Supports configuration as 8U, 12U or 22U rack. Height is 17.8", 24.8" or 42.3" and unit weight varies depending on configuration.



Find it fast! Try our interactive rack selector at www.triplite.com/wall-mount or contact our application team at **773.869.1236** or solutions@triplite.com.

Floor-Standing Open Frame Racks

Model	EIA-Compliant Rack Spaces	Maximum Device Depth	2-Post or 4-Post Mounting	Roof Panel	Stationary Weight Capacity	Rolling Weight Capacity	Casters (HD: 3" Casters)	Color (BL=Black, WH=White)	Unit Height	Unit Width	Unit Depth	Unit Weight	Equipment Mounting Holes (Square or Round/Threaded)	Assembled ¹	TAA Compliant
12U-45U 2-Post Racks – Recommended for networking applications in secure areas.															
SR2POST12	12U	36"	2-Post	No	110 lb	–	No	BL	23.2"	19.9"	11.7"	4 lb	Square	No	No
SR2POST13	13U	48"	2-Post	No	800 lb	–	No	BL	28"	20.3"	4.75" ²	20 lb	Round	No	No
SR2POST25	25U	48"	2-Post	No	800 lb	–	No	BL	49"	20.3"	4.75" ²	23 lb	Round	No	No
SR2POST	45U	48"	2-Post	No	800 lb	–	No	BL	84"	20.3"	4.75" ²	29 lb	Round	No	No
SR2POSTAA	45U	48"	2-Post	No	800 lb	–	No	BL	84"	20.3"	4.75" ²	29 lb	Round	No	Yes
12U-45U Standard-Depth 4-Post Racks – Recommended for server and networking applications in secure areas.															
SR12UBEXPNDKD	12U	36"	4-Post	No	1000 lb	1000 lb	Yes	BL	25.6"	20.37"	35.94"	45 lb	Square	No	No
SR4POST13	13U	36"	4-Post	No	1000 lb	– ³	Opt.	BL	28"	20.2"	22-36"	39 lb	Square	No	No
SR4POST25	25U	36"	4-Post	No	1000 lb	– ³	Opt.	BL	49.3"	20.2"	22-36"	45 lb	Square	No	No
SR4POST	45U	36"	4-Post	No	1000 lb	– ³	Opt.	BL	84.3"	20.2"	22-36"	54 lb	Square	No	No
SR4POST1224	45U	36"	4-Post	No	1000 lb	– ³	Opt.	BL	84.3"	20.3"	22-36"	69 lb	Round	No	No
48U-58U Heavy-Duty Standard-Depth 4-Post Racks – Recommended for high-density server and networking applications in secure areas.															
SR4POST48HD	48U	35.25"	4-Post	No	3000 lb	– ⁴	Opt.	BL	90"	24"	35.25"	110 lb	Square	No	No
SR4POST50HD	50U	35.25"	4-Post	No	3000 lb	– ⁴	Opt.	BL	93"	24"	35.25"	113 lb	Square	No	No
SR4POST52HD	52U	35.25"	4-Post	No	3000 lb	– ⁴	Opt.	BL	97"	24"	35.25"	116 lb	Square	No	No
SR4POST58HD	58U	35.25"	4-Post	No	3000 lb	– ⁴	Opt.	BL	107.5"	24"	35.25"	125 lb	Square	No	No
42U-48U Premium Heavy-Duty Standard-Depth 4-Post Racks – Recommended for high-density server and networking applications in secure areas.															
SR42UBEXPND	42U	37"	4-Post	Yes	3000 lb	2250 lb	Yes	BL	78.5"	23.63"	41.5"	142 lb	Square	Yes	No
SR42UBEXPNDNR3	42U	37"	4-Post	No	3000 lb	3000 lb	HD	BL	79.5"	23.63"	41.5"	150 lb	Square	Yes	No
SR42UWEXPNDNR3	42U	37"	4-Post	No	3000 lb	3000 lb	HD	WH	79.5"	23.63"	41.5"	150 lb	Square	Yes	No
SR45UBEXPND	45U	37"	4-Post	Yes	3000 lb	2250 lb	Yes	BL	83.75"	23.63"	41.5"	147 lb	Square	Yes	No
SR45UBEXPNDNR3	45U	37"	4-Post	No	3000 lb	3000 lb	HD	BL	84.75"	23.63"	41.5"	130 lb	Square	Yes	No
SR48UBEXPND	48U	37"	4-Post	Yes	3000 lb	2250 lb	Yes	BL	89"	23.63"	41.5"	171 lb	Square	Yes	No
SR48UBEXPNDNR3	48U	37"	4-Post	No	3000 lb	3000 lb	HD	BL	90"	23.63"	41.5"	163 lb	Square	Yes	No
42U-45U Premium Heavy-Duty Mid-Depth 4-Post Racks – Recommended for space-limited server and networking applications in secure areas.															
SR42BMDEXPNDNR3	42U	31"	4-Post	No	3000 lb	3000 lb	HD	BL	79.5"	23.63"	36"	94 lb	Square	Yes	No
SR42UBMDEXPND	42U	31"	4-Post	Yes	3000 lb	2250 lb	Yes	BL	78.5"	23.63"	36"	103 lb	Square	Yes	No
SR45UBMDEXPND	45U	31"	4-Post	Yes	3000 lb	2250 lb	Yes	BL	83.75"	23.63"	36"	140 lb	Square	Yes	No

Standards include EIA/ECA-310-E, IEC 60297-3-100, DIN 41494, UL 60950, NOM and RoHS. Standards may vary with model. Most racks include a 5-year limited warranty. See triplite.com for details. (1) Includes models that require minimal assembly. (2) Not including base. (3) 1000 lb with optional SRCASTER. (4) 3000 lb with optional SRCASTERHDKIT.



Find it fast! Try our interactive rack selector at www.triplite.com/open-frame or contact our application team at **773.869.1236** or solutions@triplite.com.

Cooling Solutions & Accessories

Model	Description
Close-Coupled, Self-Contained Air Conditioners – Rack-mount, wall-mount, portable and row-based air conditioning with network management support.	
SRCOOL2KWM	2000 BTU Wall-Mount Cabinet Air Conditioning Unit (5-15P plug. 120V input. Optional SRCOOLNET2 network card.)
SRCOOL7KRM	7000 BTU Rack-Mount Air Conditioning Unit (5-15P plug. 120V input. Optional SRCOOLNET2 network card.)
SRCOOL12K	12000 BTU Portable Air Conditioning Unit (5-15P plug. 120V input. Optional SRCOOLNET network module.)
SRCOOL18K	18000 BTU Portable Air Conditioning Unit (L6-20P plug. 208/240V input. Optional SRCOOLNET2 network card.)
SRCOOL24K	24000 BTU Portable Air Conditioning Unit (L6-20P plug. 208/240V input. Includes SRCOOLNET2 network card.)
SRCOOL33K	33000 BTU Row-Based Air Conditioning Unit (L6-30P plug. 200-240V input. Optional SNMPWEBCARD network card.)
SRXCOOL12K	12000 BTU Portable Air Conditioning Unit (CEE 7/7 plug. 230V input. Optional SRCOOLNET network module.)
SRXCOOL33K	33000 BTU Row-Based Air Conditioning Unit (42U cabinet. 200-240V hardwire input. Optional SNMPWEBCARD network card.)
Air Conditioner Accessories – Configuration kits, network management and environmental sensors.	
SRCEILINGADAPT	Ceiling Tile Adapter Kit for SRCOOL33K/SRXCOOL33K (Facilitates connection of ducts to dropped ceiling.)
SRCOOL7KDUCT	Optional Exhaust Duct Kit for SRCOOL7KRM (Required for open frame racks and area-cooling applications.)
SRCOOLNET	Network Management Module for SRCOOL12K/SRXCOOL12K (Includes ENVIROSENSE sensor.)
SRCOOLNET2	Network Management Card for SRCOOL2KWM/SRCOOL7KRM/SRCOOL18K (Includes ENVIROSENSE sensor.)
SNMPWEBCARD	Network Management Card for SRCOOL33K/SRXCOOL33K (Optional ENVIROSENSE sensor.)
ENVIROSENSE	Temperature/Humidity/Dry Contact Closure Sensor (12' cord. Requires SNMPWEBCARD.)
Chilled Water Cooling Solutions – Row-based chilled water cooling for medium- and high-density rack environments.	
SRCOOL60KCW	60 kW Row-Based Chilled Water Cooling Unit (42U half-width cabinet. 208-230V hardwire input. Includes network card.)
SRCOOL60KRT	Remote Temperature Sensor for SRCOOL60KCW
SRCOOL60KRTH	Remote Temperature and Humidity Sensor for SRCOOL60KCW
SRCOOL60KTP	Upper Pipe Installation Kit for SRCOOL60KCW
SRCOOL60KWDR	Rope-Style Water Leak Detection Sensor for SRCOOL60KCW
Active Airflow Management – High-Performance fans for rack enclosure heat removal.	
SRFAN1U	1U Fan Tray (5-15P plug. 120V input. 3 fans provide ~210 CFM upward airflow.)
SRFAN3U	3U Fan Panel (5-15P plug. 120V input. 3 fans provide ~210 CFM rearward airflow.)
SRFANROOF	Roof Fan Panel (For floor-standing enclosures. 5-15P plug. 120V input. 6 fans provide ~630 CFM upward airflow.)
SRFANWM	Roof Fan Kit (For wall-mount enclosures. 5-15P plug. 120V input. 2 fans provide ~210 CFM upward airflow.)
SRXFAN3U	3U Fan Panel (C14 inlet. 208-240V input. 3 fans provide ~315 CFM rearward airflow.)
SRXFANROOF	Roof Fan Panel (For floor-standing enclosures. C14 inlet. 208-240V input. 6 fans provide ~420 CFM upward airflow.)
Passive Airflow Management – Blanking panels, ducts and gaskets to prevent warm air recirculation and increase cooling efficiency.	
SR1UBRUSH	1U Cable Pass-Through Panel (Brush strip blocks unwanted airflow but allows cable access.)
SR1UPANEL10	10-Pack of Toolless 1U Blanking Panels (Snap into empty rack spaces to block unwanted airflow.)
SR1UPANEL50	50-Pack of Toolless 1U Blanking Panels (Snap into empty rack spaces to block unwanted airflow.)
SR1UPANEL200	200-Pack of Toolless 1U Blanking Panels (Snap into empty rack spaces to block unwanted airflow.)
SRBRUSHWM	Cable Pass-Through Panel for Wall-Mount Enclosures (Brush strip blocks unwanted airflow but allows cable access.)
SRFILTER	Air Filter Kit for 25-48U Enclosures (Attaches inside front door with hook-and-loop strips.)
SRGASKET	Enclosure Airflow Optimization Kit (Foam strips block unwanted airflow through enclosure side gaps.)
SRSKIRT	Enclosure Skirt Kit (Brush strip blocks unwanted airflow under floor-standing enclosures.)
SRSKIRT3	Enclosure Skirt Kit for Enclosures with 3" Casters (Brush strip blocks unwanted airflow under floor-standing enclosures.)
SRSWITCHDUCT	Side Airflow Duct Kit (For large network switches in floor-standing enclosures. Requires 2U above and below chassis.)
SRTHERMDUCT	Overhead Duct Kit (For standard 42-48U enclosures. Routes exhaust air to HVAC return, preventing recirculation.)
SRXUPANEL	Multi-Size Blanking Panel Kit (1U, 2U, 4U and 8U panels. Cover empty rack spaces to block unwanted airflow.)

Standards and warranties vary with model. See tripplite.com for details.



Find it fast! Try our interactive selector at www.tripplite.com/cooling or contact our application team at [773.869.1236](tel:773.869.1236) or solutions@tripplite.com.

Rack Accessories

Model	Description
Vertical Cable Managers – Keep cables organized to help prevent airflow obstructions and facilitate troubleshooting and changes.	
SRCABLEDUCTVRT	6' Vertical Duct-Type Cable Manager (Finger duct with cover. Two 3' sections. Toolless mounting.)
SRCABLERINGVRT	6' Vertical Ring-Type Cable Manager (30 flexible D-rings. Two 3' sections. Toolless mounting.)
SRCABLEVRT3	6' High-Capacity Vertical Duct-Type Cable Manager (3" finger duct. Three 2' sections. Toolless mounting.)
SRCABLEVRT6	6' High-Capacity Vertical Duct-Type Cable Manager (6" finger duct with door. Three 2' sections. Toolless mounting.)
SRCABLEVRT12	6' High-Capacity Vertical Duct-Type Cable Manager (12" finger duct with door. Three 2' sections. Toolless mounting.)
SRVRTBAR	Pair of 42U Toolless Vertical Mounting Bars (For PDUs and cable managers. Same as SR42UB bars.)
SRVRTBAR45	Pair of 45U Toolless Vertical Mounting Bars (For PDUs and cable managers. Same as SR45UB bars.)
SRVRTBAR48	Pair of 48U Toolless Vertical Mounting Bars (For PDUs and cable managers. Same as SR48UB bars.)
Horizontal Cable Managers – Route cables from vertical cable channels across the rack to equipment ports and patch panels.	
SRCABLEDUCT1U	1U Horizontal Duct-Type Cable Manager (Finger duct with cover.)
SRCABLEDUCT1UHD	1U High-Capacity Horizontal Duct-Type Cable Manager (Finger duct with cover.)
SRCABLEDUCT2UHD	2U High-Capacity Horizontal Duct-Type Cable Manager (Finger duct with cover.)
SRCABLERING1U	1U Horizontal Ring-Type Cable Manager (5 flexible D-rings and pass-through ports with blanking grommets.)
SRCABLERING2U	2U Horizontal Ring-Type Cable Manager (10 flexible D-rings and pass-through ports with blanking grommets.)
SRCABLETRAY1U	1U Horizontal Cable Management Tray (12 cable strain relief anchor points and nylon cable ties.)
Overhead Cable Managers – Route cables between racks, across aisles and over open spaces.	
SRCABLELADDER	10' x 1' Cable Ladder (2 x 5' sections. Requires SRCABLETRAY or SRLADDERATTACH for connection.)
SRCABLETRAY	Roof-Mounted Cable Trough (Provides cable routing and power/data cable separation.)
SRCABLETRAYEXP	Roof-Mounted Cable Trough Expander (Provides vertical expansion. Requires SRCABLETRAY.)
SRLADDERATTACH	Ladder Connection Kit (Connects SRCABLELADDER to a wall or open frame rack.)
Cable Ties – Bundle and secure cables.	
P350-10N-10	10-Pack of Reusable 10" Cable Ties (Hook-and-loop closure.)
P352-07N-100	100-Pack of 7.5" Nylon Cable Ties (Ratcheting "zip" closure.)
Shelves – Provide stable storage and convenient accessibility for non-rack equipment in 2-post and 4-post racks.	
SRSHELF2P	2U Cantilever Fixed Shelf (60 lb capacity. 18" depth. 2-post or 4-post mounting.)
SRSHELF2P1U	1U Cantilever Fixed Shelf (40 lb capacity. 12" depth. 2-post or 4-post mounting.)
SRSHELF2P1UTM	Toolless 1U Cantilever Fixed Shelf (30 lb capacity. 12" depth. Toolless 2-post or 4-post mounting.)
SRSHELF2PDP	2U Cantilever Fixed Shelf (60 lb capacity. 21" depth. 2-post or 4-post mounting.)
SRSHELF2PX2	2U Cantilever Fixed Shelf (Double-sided with 60 lb capacity per side. 36" depth. 2-post or 4-post mounting.)
SR16SHELF	3U Device Storage Shelf (Organizes tablets and/or laptops. 16-device capacity. 16" depth. Square-hole mounting on two rails of 4-post rack.)
SRSHELF2PTM	Toolless 2U Cantilever Fixed Shelf (50 lb capacity. 18" depth. Toolless square-hole mounting on two rails of 4-post rack.)
SRSHELF4PHD	1U Heavy-Duty Fixed Shelf (250 lb capacity. 25.5" platform depth. ¹ 4-post mounting.)
SRSHELF4PHDTM	Toolless 1U Heavy-Duty Fixed Shelf (250 lb capacity. 25.5" platform depth. ¹ Toolless 4-post mounting.)
SRSHELF4PKYBD	1U Sliding Keyboard Shelf (25 lb capacity. 16" platform depth. ¹ 4-post mounting. Holds user-supplied keyboard.)
SRSHELF4PSL	1U Sliding Shelf (50 lb capacity. 28.3" platform depth. ¹ 4-post mounting.)
SRSHELF4PSLHD	Heavy-Duty Sliding Shelf (200 lb capacity. 28.3" platform depth. ¹ 4-post mounting.)
SRSHELFKBD	1U Sliding USB Keyboard with Touchpad (Includes USB cable. 4-post mounting. 2-post mounting with B019-000.)
Side Panels – Cover open rack sides to prevent warm air recirculation, restrict access and streamline appearance.	
SR42SIDE	1 Locking Side Panel for Select 42U Enclosures (Same as SR42UB side panels.)
SR42SIDEPT	2 Locking Side Panels with Cable Pass-Through for Select 42U Enclosures (Brush strips block unwanted airflow.)
SR48SIDE	1 Locking Side Panel for Select 48U Enclosures (Same as SR48UB side panels.)
SR48SIDE4PHD	2 Latching Side Panels for 48U Heavy-Duty Open Frame Rack (Panels cover one side for end-of-row applications.)
SR50SIDE4PHD	2 Latching Side Panels for 50U Heavy-Duty Open Frame Rack (Panels cover one side for end-of-row applications.)
SR52SIDE4PHD	2 Latching Side Panels for 52U Heavy-Duty Open Frame Rack (Panels cover one side for end-of-row applications.)
SR58SIDE4PHD	3 Latching Side Panels for 58U Heavy-Duty Open Frame Rack (Panels cover one side for end-of-row applications.)

Standards and warranties vary with model. (1) Support rails can adjust to fit deeper racks.



Find it fast! Try our interactive selector at www.tripplite.com/rack-acc or contact our application team at **773.869.1236** or solutions@tripplite.com.

Rack Accessories

Model	Description
Configuration Accessories – Adapt racks for alternate/additional applications.	
SRCASTER	Caster Kit (4 casters with mounting hardware. 550 lb per caster. 2" wheels. Same as SR42UB casters.)
SRCASTERHDKIT	Heavy-Duty Caster Kit (4 casters and levelers, bolt-down brackets and hardware. 750 lb per caster. 3" wheels.)
SRCOLOKIT42U	42U Colocation Kit (Divides standard-width/depth 42U rack enclosure into 2 separate, locking 20U compartments.)
SRCOLOKIT48U	48U Colocation Kit (Divides standard-width/depth 48U rack enclosure into 2 separate, locking 23U compartments.)
SREXTENDER	Rack Enclosure Extension Frame (Increases depth of standard-width 42/48U enclosures by 8".)
SRPAGODAROOFF	Drip-Resistant Roof Panel (For standard-width/depth rack enclosures.)
Mounting Accessories – Mounting hardware, brackets, rails, adapters and grounding kits.	
2-9USTAND	Adjustable 2U to 9U Tower Stands (For most 2U+ rack-mount UPS systems. 2 units adjust from 10U to 14U.)
2POSTRMKITHD	Heavy-Duty 2-Post Rack-Mounting Kit (For 2U/3U/4U UPS systems, battery packs and transformers.)
2POSTRMKITWM	2-Post Rack-Mounting and Wall-Mounting Kit (For 2U UPS systems, battery packs and transformers.)
4POSTRAILKIT	4-Post Rack Rail/Shelf Kit (Adjustable depth. Supports rack-mounted equipment up to 250 lb. Requires 2U.)
4POSTRAILKIT1U	1U 4-Post Rack Rail/Shelf Kit (Adjustable depth. Supports rack-mounted equipment up to 150 lb.)
4POSTRAILKITHD	Heavy-Duty 4-Post Rack Rail/Shelf Kit (Adjustable depth. Supports rack-mounted equipment up to 500 lb. Requires 2U.)
4POSTRAILSM	Side-Mounted 4-Post Rack Rail/Shelf Kit (Supports rack-mounted equipment up to 250 lb without using front/rear mounting holes.)
B019-000	2-Post Console Rack-Mounting Kit (For B020-, B021-, B040- and B070-series rack consoles and console KVMs.)
PDU4PKIT	Rear Support Rail Kit (For select 1U ATS PDUs mounted in 4-post racks and rack enclosures.)
PDUMVROTATEBRKT	PDU Rotation Brackets (Toolless mounting brackets allow vertical PDU outlets to face rear of rack.)
PDUSIDEBRKT	1U PDU Vertical Mounting Kit (Allows vertical installation of select 1U PDUs, power strips and surge protectors.)
SR2319ADAPT	23" to 19" Adapter Kit (Brackets for mounting 19" rack equipment in 23" racks. Compatible with SRVTRAIL23.)
SRBOLTDOWN	Bolt-Down Hardware Kit (Secures rack bolt-down brackets or optional SRSTABILIZE anti-tip plates to facility floor.)
SRCAGENUT5MM	M5 Square Hole Rack Hardware Kit (Includes 50 M5 cage nuts, screws and washers for equipment mounting.)
SRCAGENUTS	M6 Square Hole Rack Hardware Kit (Includes 50 M6 cage nuts, screws and washers for equipment mounting.)
SRCAGENUTS1224	12-24 Square Hole Rack Hardware Kit (Includes 50 12-24 cage nuts, screws and washers for equipment mounting.)
SRGROUND	Toolless 0U Vertical Grounding Bar (75.5" copper bar has facility ground lug and 21 grounding wires for equipment.)
SRGROUNDANALBC	1U Grounding Panel (Provides connections for banana-plug and alligator-clip anti-static ESD wrist bands.)
SRPDU2PBRKT	Vertical PDU Mounting Brackets (Mount 1 or 2 vertical PDUs to rails of 2-post and 4-post open frame racks.)
SRSCREWS	Round/Threaded-Hole Hardware Kit (Includes 50 12-24 screws and washers.)
SRSTABILIZE	Anti-Tip Stabilizing Plate Kit (Stabilizes stand-alone rack enclosures. Compatible with optional SRBOLTDOWN.)
SRVTRAIL23	4 x 42U Vertical 23" Mounting Rails (Convert extra-wide 42U enclosures to mount 23" rack equipment.)
UPSHDEARKIT	Heavy-Duty UPS Mounting Ears (Support 2U rack-mounted equipment up to 65 lb from two vertical rails without rear support.)
UPSWM	UPS Wall-mount Bracket (For select tower UPS systems.)
Security & Environmental Monitoring Accessories – Locks, sensors and remote management cards.	
SRCOMBO	Combination Lock Handle Kit (For front and rear rack enclosure doors. Includes bypass key.)
SRSWITCH	Magnetic Door Switch Kit (For front and rear rack enclosure doors. Requires network management card sensor.)
MODBUSCARD	MODBUS Remote Management Card (For select SmartOnline UPS systems.)
RELAYIOCARD	Contact Closure Interface Card (For select UPS systems. Provides 6 outputs and 1 input.)
SNMPWEBCARD	Network Management Card (For select UPS systems/PDUs. Requires JRE. Supports optional ENVIROSENSE sensor.)
TLNETCARD	Network Management Card (For select UPS systems. JRE-free. Supports optional TLNETEM sensor.)
WEBCARDLX	Network Management Card (For select UPS systems/PDUs. JRE-free. Supports several optional sensors.)

Standards and warranties vary with model. See tripplite.com for details.



Find it fast! Try our interactive selector at www.tripplite.com/rack-acc or contact our application team at [773.869.1236](tel:773.869.1236) or solutions@tripplite.com.

Other Rack-Mount IT Solutions – Power Distribution Units (PDUs)

Model	Voltage	Capacity	Input Plug	Outlets	Rack Size
Basic Rack PDUs – Reliable power distribution.					
PDU1215	120V	1.8kW	5-15P	13 (5-15R)	1U or 0U (17.5")
PDU1220	120V	2.4kW	5-20P	13 (5-15/20R)	1U or 0U (17.5")
PDU1415	120V	1.8kW	5-15P	14 (5-15R)	0U Vertical (24")
PDU1420T	120V	2.4kW	L5-20P	14 (5-15/20R)	0U Vertical (24")
PDU2430	120V	2.9kW	L5-30P	24 (5-15R)	1U or 0U (17.5")
PDU12IEC	100–240V	1.6–3.8kW	C20 inlet	14 (12 C13 + 2 C19)	1U or 0U (17.5")
PDUNV	100–240V	1.6–3.8kW	6 options (C20 inlet)	14 (12 C13 + 2 C19)	1U or 0U (17.5")
PDUH20DV	100–240V	1.6-3.8kW	L6-20P (C20 inlet)	14 (12 C13 + 2 C19)	1U or 0U (17.25")
PDU1230	208/240V	4.8/5.8kW	L6-30P	20 (16 C13 + 4 C19)	1U or 0U (17.5")
PDUH20HVL6	208/240V	3.3/3.8kW	L6-20P	14 (12 C13 + 2 C19)	1U or 0U (17.25")
PDUH30HV19	208/240V	5/5.8kW	L6-30P	4 (C19)	1U or 0U (17.5")
PDUV30HV	208/240V	5/5.8kW	L6-30P	38 (32 C13 + 6 C19)	0U Vertical (63.75")
Metered Rack PDUs – Reliable power distribution and current/load monitoring.					
PDUMH15AT	120V	1.4kW	ATS: 2 x 5-15P	8 (5-15R)	1U
PDUMH20AT	120V	1.9kW	ATS: 2 x L5-20P/5-20P	16 (5-15/20R)	1U
PDUMV15	120V	1.4kW	5-15P	16 (5-15R)	0U Vertical (48")
PDUMV20	120V	1.9kW	L5-20P/5-20P	28 (5-15/20R)	0U Vertical (60")
PDUMH30	120V	2.9kW	L5-30P	12 (5-15/20R)	1U
PDUMH20HV	200-240V	3.2–3.8kW	L6-20P (C20 inlet)	10 (8 C13 + 2 C19)	1U
PDUMH20HVAT	200-240V	3.2–3.8kW	ATS: 2 x C20	10 (8 C13 + 2 C19)	1U
PDUMH30HV	208/240V	5/5.8kW	L6-30P	18 (16 C13 + 2 C19)	2U
PDUMH30HVAT	208/240V	5/5.8kW	ATS: 2 x L6-30P	19 (16 C13 + 2 C19 + L6-30R)	2U
PDUMV20HV	200–240V	3.2–3.8kW	L6-20P (C20 inlet)	38 (32 C13 + 6 C19)	0U Vertical (63.75")
PDUMV30HV	208/240V	5/5.8kW	L6-30P	30 (24 C13 + 6 C19)	0U Vertical (63.75")
PDUMV30HV2	208/240V	5/5.8kW	L6-30P	48 (40 C13 + 8 C19)	0U Vertical (70")
PDU3MV6H50	208V (3ph In)	12.6kW	50 A Hubbell CS8365C	45 (36 C13 + 9 C19)	0U Vertical (70")
Monitored Rack PDUs – Reliable power distribution, current/load monitoring and network interface.					
PDUMNH30HV	208/240V	5/5.8kW	L6-30P	16 (12 C13 + 4 C19)	2U
PDUMNV20	120V	1.9kW	L5-20P/5-20P	24 (5-15/20R)	0U Vertical (70")
PDUMNV20HV	200–240V	3.2–3.8kW	L6-20P (C20 inlet)	24 (20 C13 + 4 C19)	0U Vertical (70")
PDUMNV20HV2	200–240V	3.2–3.8kW	L6-20P (C20 inlet)	20 (18 C13 + 2 C19)	0U Vertical (35.5")
PDUMNV30HV	208/240V	5/5.8kW	L6-30P	24 (20 C13 + 4 C19)	0U Vertical (70")
PDUMNV30HV2	208/240V	5/5.8kW	L6-30P	42 (36 C13 + 6 C19)	0U Vertical (70")
Switched Rack PDUs – Reliable power distribution, current/load monitoring, network interface and remote outlet control.					
PDUMH15ATNET	120V	1.4kW	ATS: 2 x 5-15P	8 (5-15R)	1U
PDUMH15NET	120V	1.4kW	5-15P	16 (5-15R)	1U
PDUMH15NET2	120V	1.4kW	5-15P	8 (5-15R)	1U
PDUMV15NET	120V	1.4kW	5-15P	16 (5-15R)	0U Vertical (49")
PDUMH20ATNET	120V	1.9kW	ATS: 2 x L5-20P/5-20P	16 (5-15/20R)	1U
PDUMH20NET	120V	1.9kW	L5-20P/5-20P	16 (5-15/20R)	1U
PDUMH20NET2	120V	1.9kW	L5-20P/5-20P	8 (5-15/20R)	1U
PDUMV30NET	120V	2.9kW	L5-30P	24 (5-15/20R)	0U Vertical (70")
PDUMH15HVNET	200–240V	2.3–2.9kW	C14 inlet	8 (C13)	1U
PDUMH20HVATNET	200–240V	3.2–3.8kW	ATS: 2 x C20 (C20 inlets)	10 (8 C13 + 2 C19)	1U
PDUMH20HVNET	200–240V	3.2–3.8kW	L6-20P (C20 inlet)	8 (C13)	1U
PDUMH30HV19NET	208/240V	5.8kW	L6-30P	14 (8 C13 + 6 C19)	2U
PDUMV20HVNET	200–240V	3.2–3.8kW	L6-20P (C20 inlet)	24 (20 C13 + 4 C19)	0U Vertical (70")
PDUMV20HVNET2	200–240V	3.2–3.8kW	L6-20P (C20 inlet)	8 (7 C13 + 1 C19)	0U Vertical (39")
PDUMV30HVNET	208/240V	5/5.8kW	L6-30P	24 (20 C13 + 4 C19)	0U Vertical (70")
PDUMVR30HVNET	208/240V	5/5.8kW	L6-30P	24 (20 C13 + 4 C19)	0U Vertical (70")

Standards and warranties vary with model. Capacity varies with voltage, applicable derating and load balancing. See tripplite.com for details.



Find it fast! Try our interactive PDU selector at www.tripplite.com/pdu or contact our application team at [773.869.1236](tel:773.869.1236) or solutions@tripplite.com.

Other Rack-Mount IT Solutions – KVM/Console Solutions

Model	Description
Rack Consoles – LCD console folds and slides into 1U drawer for compact storage and rack-side access.	
B021-000-17	1U Rack-Mount Console with 19" LCD
B021-000-19	1U Rack-Mount Console with 19" LCD
B021-000-19-HD	1U Rack-Mount Console with 19" LCD, DVI or VGA
Console KVM Switches – KVM switch with LCD console folds and slides into 1U drawer for compact storage and rack-side access.	
B020-008-17	8-Port 1U Rack-Mount Console KVM Switch with 17" LCD
B020-016-17	16-Port 1U Rack-Mount Console KVM Switch with 17" LCD
B020-016-17-IP	16-Port 1U Rack-Mount Console KVM Switch with 17" LCD and IP Remote Access
B020-U08-19-IP	8-Port 1U Rack-Mount Console KVM Switch with 19" LCD and IP Remote Access
B020-U08-19-K	8-Port 1U Rack-Mount Console KVM Switch with 19" LCD + 8 PS2/USB Combo Cables
B020-U16-19-IP	16-Port 1U Rack-Mount Console IP KVM Switch with 19" LCD
B020-U16-19-K	16-Port 1U Rack-Mount Console KVM Switch with 19" LCD + 8 PS2/USB Combo Cables
B040-008-19	8-Port 1U Rack-Mount Console KVM Switch with 19" LCD
B040-016-19	16-Port 1U Rack-Mount Console KVM Switch with 19" LCD
B070-008-19	8-Port Cat5 1U Rack-Mount Console KVM Switch with 19" LCD
B070-008-19-IP	8-Port Cat5 1U Rack-Mount 1+1 User Console KVM Switch with 19" LCD and IP Remote Access
B070-016-19	16-Port Cat5 1U Rack-Mount Console KVM Switch with 19" LCD
B070-016-19-IP	16-Port Cat5 1U Rack-Mount 1+1 User Console KVM Switch with 19" LCD and IP Remote Access

Standards and warranties vary with model. See tripplite.com for details.



Find it fast! Try our interactive KVM selector at www.tripplite.com/kvm or contact our application team at **773.869.1236** or solutions@tripplite.com.

Other Rack-Mount IT Solutions – UPS Systems

Model	VA	Watts	Plug	AC Output	Outlets	½ Load Runtime ¹	LCD	Size/Depth ²
SmartPro UPS Systems – Line-interactive operation (AVR), sine wave output, battery backup and network card slot.								
SMART1000RM1U	1 kVA	800 W	5-15P	120V	6 (5-15R)	14 min (400 W)	No	1U/19.8"
SMART1500RM2U	1.5 kVA	1.35 kW	5-15P	120V	8 (5-15R)	13 min (675 W)	Yes	2U/16.5"
SMART1500RML2UA	1.5 kVA	1.35 kW	5-15P	120V	8 (5-15R)	14 min+ (675 W)	Yes	2U/20"
SMART2200RM2U	2.2 kVA	1.92 kW	5-20P	120V	8 (4 5-15R+4 5-20R)	12 min (960 W)	Yes	2U/24.5"
SMART2200RML2U	2.2 kVA	1.92 kW	5-20P	120V	8 (4 5-15R+4 5-20R)	12 min+ (960 W)	Yes	2U/26.3"
SMART3000RM2U	3 kVA	2.25 kW	L5-30P	120V	9 (8 5-20R+L5-30R)	10 min+ (1.125 kW)	Yes	2U/26.5"
SMART3000RML2U	3 kVA	2.88 kW	L5-30P	120V	9 (8 5-20R+L5-30R)	10 min+ (1.44 kW)	Yes	2U/26"
SmartOnline UPS Systems – On-line operation (double conversion), sine wave output, battery backup and network card slot.								
SU1000RTL2UA	1 kVA	800 W	5-15P	120V	6 (5-15R)	14 min+ (400 W)	No	2U/16.5"
SU1500RTL2UA	1.5 kVA	1.2 kW	5-15P	120V	6 (5-15R)	14 min+ (600 W)	No	2U/26"
SU1500RTLCD2U	1.5 kVA	1.35 kW	5-15P	120V	6 (5-15R)	14 min+ (675 W)	Yes	2U/25.5"
SU2200RTL2UA	2.2 kVA	1.6 kW	5-20P	120V	7 (6 5-15/20R+L5-20R)	14 min+ (800 W)	No	2U/26"
SU2200RTLCD2U	2.2 kVA	1.8 kW	5-20P	120V	7 (6 5-15/20R+L5-20R)	12 min+ (900 W)	Yes	2U/26"
SU3000RTL2U	3 kVA	2.5 kW	L5-30P	120V	7 (6 5-15/20R+L5-30R)	15 min+ (1.25 kW)	No	2U/37"
SU3000RTL3U	3 kVA	2.4 kW	L5-30P	120V	9 (4 5-15R+4 5-15/20R+L5-30R)	14 min+ (1.2 kW)	No	3U/37"
SU3000RTLCD2U	3 kVA	2.7 kW	L5-30P	120V	9 (4 5-15R+4 5-15/20R+L5-30R)	11.3 min+ (1.35 kW)	Yes	2U/36.5"
SU3000RTLCD3U	3 kVA	2.7 kW	L5-30P	120V	9 (4 5-15R+4 5-15/20R+L5-30R)	11 min+ (1.35 kW)	Yes	3U/37"
SmartOnline Hot-Swappable UPS Systems – On-line operation (double conversion), sine wave output, battery backup, network card slot and bypass switch.								
SU6000RT4UHV	6 kVA	5.4 kW	L6-30P	200-240V	4 (2 L6-20R+2 L6-30R)	8.5 min+ (2.7 kW)	Yes	4U/28.7"
SU8000RT3U	8 kVA	7.2 kW	Hardwire	200-240V	6 (2 L6-30R + 4 L6-20R)	13.5 min+ (3.6 kW)	Yes	6U/37.5"
SU10KRT3UHV	10 kVA	9 kW	Hardwire	200-240V	Hardwire	12.5 min+ (4.5 kW)	Yes	6U/37.5"

Standards and warranties vary with model. See tripplite.com for details. (1) Runtime varies with load, application, battery condition and other factors. Models with "+" support expandable runtime with optional external battery packs. (2) Minimum rack depth required for installation.



Find it fast! Try our interactive UPS selector at www.tripplite.com/ups or contact our application team at **773.869.1236** or solutions@tripplite.com.

Other Rack-Mount IT Solutions – Patch Panels

Model	Description
Copper Patch Panels – Reliable, compatible, space-saving connections for UTP/STP Ethernet patch cables.	
N050-012	12-Port Wall-Mount Cat5e Patch Panel, 568B, RJ45 Ethernet
N052-012	12-Port 1U Rack-Mount Cat5e 110 Patch Panel, 568B, RJ45 Ethernet
N052-024	24-Port 1U Rack-Mount Cat5e 110 Patch Panel, 568B, RJ45 Ethernet
N052-048	48-Port 2U Rack-Mount Cat5e 110 Patch Panel, 568B, RJ45 Ethernet
N052-048-1U	48-Port 1U Rack-Mount High-Density Cat5/5e 110 Patch Panel, 568B, RJ45 Ethernet
N054-024	24-Port 1U Rack-Mount Cat5e Feed-Through Patch Panel, RJ45 Ethernet
N250-012	12-Port Cat6/Cat5 Wall-Mount Vertical 110 Patch Panel
N250-024-LP	24-Port Cat6/Cat5 Low-Profile Feed-Through Patch Panel, 1U Rack-Mount/Wall-Mount
N252-012	12-Port 1U Rack-Mount Cat6/Cat5 110 Patch Panel 568B, RJ45 Ethernet
N252-024	24-Port 1U Rack-Mount Cat6/Cat5 110 Patch Panel, 568B, RJ45 Ethernet
N252-024-HU	24-Port 0.5U Rack-Mount Cat6/Cat5 110 Patch Panel 568B, RJ45 Ethernet
N252-048	48-Port 2U Rack-Mount Cat6/Cat5 110 Patch Panel, 568B, RJ45 Ethernet
N252-048-1U	48-Port 1U Rack-Mount Cat6/Cat5 High Density 110 Patch Panel, 568B, RJ45 Ethernet
N254-024	24-Port 1U Rack-Mount Cat6/Cat5 Feed-Through Patch Panel, RJ45 Ethernet
N254-024-6A	24-Port 1U Rack-Mount Cat6a Feed-Through Patch Panel, RJ45 Ethernet
N254-024-SH	24-Port 1U Rack-Mount STP Shielded Cat6/Cat5 Feed-Through Patch Panel, RJ45 Ethernet
N254-024-SH-6A	24-Port 1U Rack-Mount STP Shielded Cat6a Feed-Through Patch Panel, RJ45 Ethernet
N254-024-SH-D	24-Port 1U Rack-Mount STP Shielded Cat5e/6 Feed-Through Patch Panel w/90° Down-Angle Ports, RJ45 Ethernet
N254-048-SH-6A	48-Port 1U Rack-Mount STP Shielded Cat6a Feed-Through Patch Panel, RJ45 Ethernet
Fiber Patch Panels – Reliable, compatible, space-saving connections for multimode and singlemode fiber-optic patch cables.	
N490-016-LCLC	16-Port Fiber Patch Panel, 1U Rack-Mount, LC/LC, Multimode or Singlemode
N490-016-SCSC	16-Port Fiber Patch Panel, 1U Rack-Mount, SC/SC, Multimode or Singlemode
N490-016-STST	16-Port Fiber Patch Panel, 1U Rack-Mount, ST/ST, Multimode or Singlemode
N492-036-LCLC-E	36-Port Fiber Patch Panel Enclosure, 1U Rack-Mount, LC/LC, Multimode or Singlemode
Modular Patch Panels – Future-proof high-density network connections with modular media cassettes (copper and fiber).¹	
N482-01U	High-Density Fiber Enclosure Panel, 1U Rack-Mount, 5-Cassette ¹ Capacity
N482-02U	High-Density Fiber Enclosure Panel, 2U Rack-Mount, 14-Cassette ¹ Capacity
N484-00U	High-Density Copper/Fiber Cassette Sleeve, 0U Magnetic Attachment, 1-Cassette ¹ Capacity
N484-01U	High-Density Copper/Fiber Enclosure Panel, 1U Rack-Mount, 4-Cassette ¹ Capacity

Standards and warranties vary with model. See tripplite.com for details. (1) See the complete line of mix-and-match modular media cassettes at tripplite.com.



Find it fast! Try our interactive selector at www.tripp-lite.com/patch or contact our application team at **773.869.1236** or solutions@tripp-lite.com.

Tripp Lite manufactures over 3,500 different IT solutions. See the complete line at www.tripp-lite.com.

Distributed By:



Tripp Lite World Headquarters

1111 W. 35th Street, Chicago, IL 60609 USA

773.869.1236 • www.tripp-lite.com

Copyright © 2017 Tripp Lite. SmartRack is a registered trademark of Tripp Lite. All other trademarks are the property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.